






公差/General tolerances(mm)		0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	3	6	10	18	30	50	80	120	180	250	315	400	500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±2	±2



5	Spring	Stainless steel	
4	Clamp	Copper Alloy	Sn Plated
3	Button	PA66	UL94V-0
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES



UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/10	/	300/10
EC 标准/IEC Standard:	III/2		
过压类别/Overvoltage Category/污染等级	III/2		
级/Pollution Degree	320/20		
额定电压/电流/Rated Voltage(V)/Current(A)	320/20		
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4.0		
线在范围(导线和导线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/26~12		
间距/Pitch(mm)/线数范围/Poles	5.0/02~24P		
剥线长度/Stripping length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		

MATERIAL: /
 MAT NO.: /
 STATUS: /

宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

APPD: LIGL 2020.06.13
 CHKD: MoEK 2020.06.13
 DRFT: LZT 2013.01.13

NAME: 2EDGKDF-5.0-XXP-1Y-00A(H)
 DRAWING NO.: 2EDGKDF-5.0-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE