



### 型号说明

RM-EBBH-2006-M-1000-00A(H)

弯插头

包塑式

系列名称

公端

线长300mm

通用型环保产品

产品插针数量  
功率针2pin,  
信号针6pin

公差/General Tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
未注公差/General Tolerances(mm)	0	~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.50	±2.20	±2.50	±2.50	±2.50	±2

额定电压/Rated Voltage	72VDC/100A
绝缘电阻/Insulation resistance	≥500MΩ
插拔次数/Mechanical working life(repeating cycles)	3000
耐电压/Withstanding voltage	1500V AC
使用温度范围/Operating temperature(°C)	-40~+105
防水等级/Levels of protection	✓
接线方式/Terminal	Soldering
导线规格范围/Wire range(mm)	Power: 4~6AWG

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRT: Eric 2021.10.13

DRT: Eric 2021.10.13

**DEGSON** 宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: RM-EBBH-2006-M-1000-00A(H)

DRAWING NO.: /

TYPE: CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRT	DATE
(10)				

REV	SHEET
T0	1/1

REV	ECN	DESCRIPTION	DRT	DATE
(10)				

SCALE: 2:1