

## Visión general

## Información del Producto

**Bus IO-DF750-002-11-2001A(H)-30050000130**

Card type IO shell,can be equipped with RJ45 connector,LED indicator

## Ventajas del producto

- ☒ Dual network port with light RJ45 interface
- ☒ 8-bit address interface
- ☒ Internal bus through 6 gold-plated terminals at the bottom
- ☒ Equipped with 8 channels power module, each node is equipped with LED
- ☒ Two internal gold-plated blade connectors are used for power cascade expansion
- ☒ Can be installed on DIN rail

## Certificación del producto

## Datos técnicos

## Dibujo del producto

## Modelo 3D

□

## Dimension

|        |        |
|--------|--------|
| length | 93.5mm |
| width  | 48mm   |
| Height | 69mm   |

## Mechanical parameters

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| structure type            | Compact terminal module housing with signal LED |
| Material                  | PC+PA66                                         |
| installation              | DIN35 rail                                      |
| Side by side installation | Dovetail groove clamping                        |

|       |                       |
|-------|-----------------------|
| label | Laser screen printing |
| color | C1 gray               |

#### Environmental data

|                                           |           |
|-------------------------------------------|-----------|
| Ambient temperature (operation)           | -40℃～+70℃ |
| Ambient temperature (storage / transport) | -40℃～+70℃ |

#### Connection method(IO)

|                                     |                               |
|-------------------------------------|-------------------------------|
| wiring                              | Spring type wiring technology |
| Strip length                        | 8-9mm                         |
| Power contacts                      | 2 blade contacts              |
| Power load                          | 10A                           |
| Rated current                       | Power: 24V Bus connector: 5V  |
| Cross section                       | 0.2~2.5mm <sup>2</sup>        |
| Connectable guide cross section AWG | 28~12AWG                      |
| PCB thickness                       | 1.0mm                         |

#### Accesorios

##### Accessories

|            |                       |
|------------|-----------------------|
| IO housing | DF750-200-11-2001A(H) |
|------------|-----------------------|

#### Datos empresariales

|                                  |             |
|----------------------------------|-------------|
| Número de pedido                 | 30050000130 |
| Unidad de embalaje               | 20          |
| Cantidad mínima de pedido        | 20          |
| Peso del producto (sin embalaje) | 122.5       |

