

Visión general

Información del Producto



Interface module-DT075-00A(H)-30040000073

Power module, power extension, with screw connector, can be installed on DIN35 rail

Ventajas del producto

Power distribution

Screw connection

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Dimension

length	65.6mm
width	57mm
Height	42mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	10A
Signal points	2
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	4
spacing	5.08mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	18
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Accesorios

Datos empresariales

Número de pedido	30040000073
Unidad de embalaje	2
Cantidad mínima de pedido	10
Peso del producto (sin embalaje)	110