

Visión general

Información del Producto



Interface module-DM50-FCN-40-40-4Y-00A(H)-30040000054

FCN module,input/output module,with screw connector and FCN Stitching line,can be installed on DIN35 rail,40 positions

Ventajas del producto

1:1 connection
Screw connection

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Dimension

length	111mm
width	57mm
Height	42mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	40
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	FCN connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	40
screw thread	M3
Hard wire cross section	1.0 mm² ... 2.5 mm²

Accesorios	
Accessories	
Wire harness	DX210-5S-500-00A(H)

Datos empresariales	
Número de pedido	30040000054
Unidad de embalaje	1
Cantidad mínima de pedido	10
Peso del producto (sin embalaje)	160