

Visión general

Información del Producto



Interface module-DM50-DBJ-09-09-4Y-00A(H)-30040000001

D-SUB module,input/output module,with screw connector and D-SUB female connector,can be installed on DIN35 rail,9 positions

Ventajas del producto

9digits to 50digits

1:1 connection

Screw connection

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

Dimension

length	65.5mm
width	57mm
Height	31mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3

Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	2A
Signal points	9
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	D-SUB connection
Connection volume	1
Number of digits	9
spacing	2.77mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	10
screw thread	M3

Hard wire cross section

1.0 mm² ... 2.5 mm²

Accesorios

Datos empresariales

Número de pedido	30040000001
Unidad de embalaje	6
Cantidad mínima de pedido	12
Peso del producto (sin embalaje)	80