

Visión general

Información del Producto



Relay module-DM72-RMUS-08-PN-1-44-01A(H)-30030000034

Subminiature Relay Module, with relay Socket , 16 relays can be installed, with relay Socket, with indicator light, Honfa relay, PNP or NPN signal can be input

Ventajas del producto

- ☒ Each signal channel and power supply voltage have LED status indicators
- ☒ Pluggable subminiature relay, with a set of normally open contacts, one-to-one output at the output
- ☒ Suitable for NPN, PNP controller
- ☒ Freewheeling diode for each signal path

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Overview

Installation location	Arbitrary
Number of channels	8
Shell Insulation Materials	PVC/PA66
color	green

Dimension

length	60mm
width	90mm
Height	60mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Output technical data

Contact type	1NO
Maximum switching voltage	240VAC 30VDC
Limit continuous current	5A
Fault monitoring (open circuit/short circuit)	no

Output connection data

Connection name	Output
Connection method	Screw connection
Stripping length	6-7mm
screw thread	M3
Connection volume	1
Number of digits	16
Hard wire cross section	1.0 ... 2.5mm ²
Cross section of flexible conductor	1.0 ... 2.5mm ²
Connectable guide cross section AWG	28 ... 12AWG

Enter connection data

Rated input voltage	24VDC
Relative to UN input voltage range	0.9....1.1
Protected name	Polarity protection

Protection circuit/component	Polarity protection diode
Status display/channel	green
Connection name	input
Connection method	screw connection
Stripping length	6-7mm
screw thread	M3
Connection volume	1
Number of digits	10
Hard wire cross section	1.0 ... 2.5mm ²
Cross section of flexible conductor	1.0 ... 2.5mm ²
Connectable guide cross section AWG	28...12AWG

Accesorios

Datos empresariales

Número de pedido	30030000034
Unidad de embalaje	4
Cantidad mínima de pedido	4
Peso del producto (sin embalaje)	128