

Visión general

Información del Producto



40A-GM-6.0-92116900062

40A silver gold male pins,Adapter wire specification6.0mm²

Ventajas del producto

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Material	Copper alloy
Plating material	Silver plated

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	6.0mm²
Conductor cross sections(AWG)	10AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	9.6mm
working life-mating cycles	≥500

Accesorios

Datos empresariales

Número de pedido	92116900062
Unidad de embalaje	
Cantidad mínima de pedido	100
Peso del producto (sin embalaje)	3.142