

Visión general

Información del Producto

**40A-SM-2.5-92116900082**40A silver plating male pins,Adapter wire specification2.5mm²

Ventajas del producto

- ✓High-precision turning process, stable and reliable products;
- ✓Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ✓Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Material	Copper alloy
Plating material	Silver plated

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	2.5mm²
Conductor cross sections(AWG)	14AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥2μm
Temperature range	-40℃~+125℃
Strip length	9mm
working life-mating cycles	≥500

Accesorios

Datos empresariales

Número de pedido	92116900082
Unidad de embalaje	
Cantidad mínima de pedido	100
Peso del producto (sin embalaje)	3.142