


Visión general

Información del Producto

**DMK-003-F(2.5-8mm²)-21020000267**

Heavy-duty insert, Number of contacts: 3, Dimension: 1 module Spaces, Rated voltage : 690V, Rated current: 40A, Female insert, axial Screw connector

Ventajas del producto

- ✓ Axial Screw connection technology, applicable to a wide range of wire specifications;
- ✓ Less materials, easy to manage;
- ✓ Modular products, easy to assemble and maintain .

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Marking

classification

Insert

Series

DM

versions

Connection method

Axial screw connection

Female/Male

Female

Dimension

1 module

Number of positions

3

PE Contacts

No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	40A
	690V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	5-11mm
Rated torque	1.5N.m(2.5/4mm²) 2N.m(6/10mm²)
Conductor cross sections (mm²)	2.5-8mm²
Conductor cross sections(AWG)	14-9AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accesorios

Accessories

Screwdriver

/

Datos empresariales

Número de pedido	21020000267
Unidad de embalaje	
Cantidad mínima de pedido	5
Peso del producto (sin embalaje)	30.12