


Visión general

Información del Producto

**DMK7-002-M(6-16mm²)-21020000274**

Heavy-duty insert, Number of contacts: 2, Dimension: 1 module Spaces, Rated voltage : 1000V, Rated current: 70A, Male insert, axial Screw connector

Ventajas del producto

- ✓ Axial Screw connection technology, applicable to a wide range of wire specifications;
- ✓ Less materials, easy to manage;
- ✓ Modular products, easy to assemble and maintain .

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Marking

classification

Insert

Series

DM

versions

Connection method

Axial screw connection

Female/Male

Male

Dimension

1 module

Number of positions

2

PE Contacts

No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	70A
	1000V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.5mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Rated torque	2N.m(6mm²) 3N.m(10mm²) 4N.m(16mm²) 5N.m(22mm²)
Conductor cross sections (mm²)	6-16mm²
Conductor cross sections(AWG)	10-6AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accesorios

Accessories

Screwdriver	/
-------------	---

Datos empresariales	
Número de pedido	21020000274
Unidad de embalaje	
Cantidad mínima de pedido	5
Peso del producto (sin embalaje)	31.5