


Visión general

Información del Producto



DE-024-MS-21020000041

Heavy-duty insert, Number of contacts: 24+PE, Dimension: 24B, Rated voltage : 500V, Rated current: 16A, Male insert, Cage clamp connector

Ventajas del producto

- ☑ Spring cage connection technology, high vibration resistance;
- ☑ No special tools required, maintenance-free ;
- ☑ Less materials, easy to manage;
- ☑ With grounding protection.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Marking

classification	Insert
Series	DE

versions

Connection method	Spring cage connection
Female/Male	Male
Dimension	24B
Number of positions	24
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	500V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7-9mm
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accesorios

Accessories

Screwdriver

/

Datos empresariales

Número de pedido	21020000041
Unidad de embalaje	
Cantidad mínima de pedido	5
Peso del producto (sin embalaje)	110.14