


Visión general

Información del Producto



DA-032-MC-21020000166

Heavy-duty insert, Number of contacts: 32+PE, Dimension: 16A, Rated voltage : 250V, Rated current: 16A, Male insert, Crimping connector

Ventajas del producto

- ✓Crimping connection technology, high wiring efficiency
- ✓Suitable for vibration occasions;
- ✓The wiring harness can be pre-installed;
- ✓Choose contacts with different wire diameters and coatings;
- ✓High-density pins, saving installation space;
- ✓With grounding protection.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D



Marking

classification	Insert
Series	DA

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	16A
Number of positions	32

PE Contacts	Yes
-------------	-----

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	250V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7.5mm
Conductor cross sections（mm²）	0.14-4.0mm²
Conductor cross sections(AWG)	26-12AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessories

Crimping tool Removal tool	/
----------------------------	---

Datos empresariales

Número de pedido	21020000166
Unidad de embalaje	
Cantidad mínima de pedido	5
Peso del producto (sin embalaje)	48