


## Visión general

### Información del Producto



### WS10-SD-PE-11030000022

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 24 - 8, Width: 10 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

### Ventajas del producto

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Grounding structure, protection circuit;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### Certificación del producto



## Datos técnicos

### Dibujo del producto

### Modelo 3D

□

### Overview

|                                           |                        |
|-------------------------------------------|------------------------|
| Connection method                         | spring-cage connection |
| Number of rows                            | 1                      |
| number of connections                     | 2                      |
| Open-end side panels                      | Yes                    |
| Insulation Materials                      | PA                     |
| Flame retardant grade, in line with UL 94 | V0                     |

### Dimension

|                  |        |
|------------------|--------|
| NS 35/7,5 Height | 49mm   |
| End plate width  | 2.5mm  |
| NS 35/15 Height  | 56.5mm |
| length           | 52mm   |
| width            | 10mm   |
| Height           | 41.5mm |

#### Wiring data

|                                   |                       |
|-----------------------------------|-----------------------|
| Strip length                      | 13~14mm               |
| Conductor cross section solid     | 0.2~10mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~10mm <sup>2</sup> |
| Conductor cross section solid AWG | 24~8                  |

#### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

#### IEC Electrical parameters

|                     |     |
|---------------------|-----|
| Rated surge voltage | 8KV |
|---------------------|-----|

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

#### Accesorios

##### Marker

|                |            |
|----------------|------------|
| Top marker     | /          |
| Side marker    | ZB10 / WB5 |
| Marker support | /          |

|               |       |
|---------------|-------|
| Warning cover | EEA10 |
|---------------|-------|

#### Accessories

|                                                    |           |
|----------------------------------------------------|-----------|
| Slotted screwdriver size (Blade thickness x Width) | 0.8×5.5   |
| Adjacent jumper (2P)                               | /         |
| Alternate jumper (2P)                              | /         |
| Staggered jumper (2P)                              | /         |
| End cover                                          | D-WS10-SD |

#### Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZB10  |
| Marker cards  | DBE-1 |

#### Accessories

|           |                      |
|-----------|----------------------|
| End cover | D-WS10-SD            |
| End clamp | E-WS                 |
| DIN rail  | NS35/7.5-1000-00A(H) |

#### Datos empresariales

|                                  |             |
|----------------------------------|-------------|
| Número de pedido                 | 11030000022 |
| Unidad de embalaje               | 50          |
| Cantidad mínima de pedido        | 50          |
| Peso del producto (sin embalaje) | 23.88       |

