

Visión general

Información del Producto



WS2.5-MID-CO-11030000157

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 24 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 2.5 mm², AWG: 28 - 12, Width: 6 mm, Color: gray, Mounting type: Panel installation

Ventajas del producto

- ☒ spring-cage connection technology, good anti-vibration performance;
- ☒ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☒ Panel installation, no need to install on the guide rail;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Overview

Connection method	spring-cage connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

End plate width	4mm
length	32mm
width	6mm
Height	22.00mm

Wiring data

Strip length	8~9mm
Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
Conductor cross section solid AWG	28~14

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	800V
Rated current (III / 3)	24A
Rated surge voltage	8KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Accesorios

Marker

Top marker	ZW5
Side marker	/
Marker support	/

Warning cover	/
---------------	---

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.5×3.5
Adjacent jumper (2P)	/
Alternate jumper (2P)	/
Staggered jumper (2P)	/
End cover	D-WS2.5-MID-CO

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Accessories

End cover	D-WS2.5-MID-CO
Bridge	WFE-2.5

Marking & Installation

Marking strip	ZW5
---------------	-----

Datos empresariales

Número de pedido	11030000157
Unidad de embalaje	200
Cantidad mínima de pedido	200
Peso del producto (sin embalaje)	3.712