


## Visión general

### Información del Producto



## WS2.5T-DIN15-11030000226

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 24 A, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 28 - 12, Width: 10 mm, Color: gray, Mounting type: NS 15

### Ventajas del producto

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### Certificación del producto



## Datos técnicos

### Dibujo del producto

### Modelo 3D

□

### Overview

|                                           |                        |
|-------------------------------------------|------------------------|
| Connection method                         | spring-cage connection |
| Number of rows                            | 1                      |
| number of connections                     | 4                      |
| Open-end side panels                      | Yes                    |
| Insulation Materials                      | PA                     |
| Flame retardant grade, in line with UL 94 | V0                     |

### Dimension

|                 |     |
|-----------------|-----|
| End plate width | 4mm |
|-----------------|-----|

|        |         |
|--------|---------|
| length | 32mm    |
| width  | 10mm    |
| Height | 28.50mm |

#### Wiring data

|                                   |                        |
|-----------------------------------|------------------------|
| Strip length                      | 8~9mm                  |
| Conductor cross section solid     | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~14                  |

#### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

#### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 24A  |
| Rated surge voltage     | 8KV  |

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

#### Accesorios

##### Marker

|                |     |
|----------------|-----|
| Top marker     | ZW5 |
| Side marker    | /   |
| Marker support | /   |
| Warning cover  | /   |

Accessories

|                                                    |                |
|----------------------------------------------------|----------------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5        |
| Adjacent jumper (2P)                               | /              |
| Alternate jumper (2P)                              | /              |
| Staggered jumper (2P)                              | /              |
| End cover                                          | D-WS2.5-MID-CO |

Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZW5   |
| Marker cards  | DBE-1 |

Accessories

|           |                  |
|-----------|------------------|
| End cover | D-WS2.5-MID-CO   |
| Bridge    | WFE-2.5          |
| End clamp | E-WS             |
| DIN rail  | NS15-1000-00A(H) |

Datos empresariales

|                                  |             |
|----------------------------------|-------------|
| Número de pedido                 | 11030000226 |
| Unidad de embalaje               | 50          |
| Cantidad mínima de pedido        | 50          |
| Peso del producto (sin embalaje) | 6.152       |

