


Visión general

Información del Producto



DS10-PE-11040000009

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm² - 16 mm², AWG: 20 - 6, Width: 10.2 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

Ventajas del producto

- ☒ Push-in connection technology, tool-free operation, more convenient and faster;
- ☒ With orange wire button, one word or cross screwdriver can release wire.
- ☒ Optional marker to avoid wire mis-inserting.
- ☒ Equipped with test holes for easy testing of the circuit.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Overview

Connection method	Push in connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

NS 35/7,5 Height	51.1mm
------------------	--------

End plate width	1.5mm
NS 35/15 Height	58.6mm
length	67.7mm
width	10.2mm

Wiring data

Strip length	16~18mm
Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~10mm ²
Conductor cross section solid AWG	20~6

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Accesorios

Marker

Top marker	ZB10 / ZS10
Side marker	ZSF10
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	1x5.5
---	-------

Bridge	/
End cover	D-DS10

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Datos empresariales

Número de pedido	11040000009
Unidad de embalaje	20
Cantidad mínima de pedido	20
Peso del producto (sin embalaje)	29.725