


Visión general

Información del Producto



DS4-QU-PE-11040000049

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, Width: 6.2 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

Ventajas del producto

- ☒ Push-in connection technology, tool-free operation, more convenient and faster;
- ☒ With orange wire button, one word or cross screwdriver can release wire.
- ☒ Optional marker to avoid wire mis-inserting.
- ☒ Equipped with test holes for easy testing of the circuit.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Overview

Connection method	Push in connection
Number of rows	1
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

NS 35/7,5 Height	36.8mm
------------------	--------

End plate width	2.2mm
NS 35/15 Height	44.3mm
length	77mm
width	6.2mm

Wiring data

Strip length	10~12mm
Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~4mm ²
Conductor cross section solid AWG	24~10

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Accesorios

Marker

Top marker	ZB6 / ZS6
Side marker	ZSF6
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
---	---------

Bridge	/
End cover	D-DS4-QU

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Datos empresariales

Número de pedido	11040000049
Unidad de embalaje	50
Cantidad mínima de pedido	50
Peso del producto (sin embalaje)	13.712