

Visión general

Información del Producto



SP-M12A-03P-MM-SF8002-20030001232

Sensor/Actuator Female socket,M12,Coding A,Unshielded,Rear panel installation/M16*1.5 Thread mounted,180° vertical pins

Ventajas del producto

- ☒ Sealing optimization, protection level up to IP68
- ☒ Meet the harsh environment
- ☒ Suitable for various occasions connection technology
- ☒ Compatible with the international and domestic same series products

Certificación del producto



RoHS

REACH



Datos técnicos

Dibujo del producto

Modelo 3D

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP68

General parameters

Rated current

4A

250V

Number of potentials

3

Insulation resistance

≥ 100 MΩ

Error-proof coding

A-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Rear board installation

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Accesorios

Accessories

Sealing cap	CAP-M12-FP-8003
-------------	-----------------

Datos empresariales

Número de pedido	20030001232
Unidad de embalaje	/
Cantidad mínima de pedido	100
Peso del producto (sin embalaje)	/

