

Visión general

Información del Producto



SD-M12S-04P-FF-SH8A50-20030001213

Sensor/Actuator Female socket,M12,Coding S,Front panel installation/PG9
Thread mounted,With 0.5m litz wires,

Ventajas del producto

- ☒ Sealing optimization, protection level up to IP68
- ☒ Meet the harsh environment
- ☒ Suitable for various occasions connection technology
- ☒ Compatible with the international and domestic same series products

Certificación del producto

RoHS REACH

Datos técnicos

Dibujo del producto

Modelo 3D

□

Dimension

Cable length

0.5m

Environmental conditions

Ambient temperature

-25℃...80℃

IP class

IP68

General parameters

Rated current

12A

630V

Number of potentials

4

Insulation resistance	≥ 100 MΩ
Error-proof coding	S-Code
Overvoltage level	II
Pollution level	3
Connection method	Single wire
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-111
--------------------------	-----------------

Cable

UL AWM form	UL1015
Cross section	1.31mm²
AWG signal wire	16AWG
Wire structure Signal wire	26/0.254mm²
Core diameter (including insulation layer)	3.1±0.05mm
Wire color	1 Black1 2 Black2 3 Black3 PE Yellow /Green
Thickness, insulation	0.73mm

Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	10MΩ
Conductor resistance	Maximum 14.6Ω/km (at 20 °C)
Nominal cable voltage	600V
Cable test voltage	2000V

Accesorios

Accessories

Sealing cap	CAP-M12-MP-8002
-------------	-----------------

Datos empresariales

Número de pedido	20030001213
Unidad de embalaje	/
Cantidad mínima de pedido	100
Peso del producto (sin embalaje)	/