

Visión general

Información del Producto



DGR100-20A(H)-12010000308

Transfer barrier terminal blocks, Rated current: 130A. Rated voltage (UL) : 600V, Cross section: 20~2AWG, pitch: 25mm, Color: black, Contact surface: Tin

Ventajas del producto

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Provide the cabinet and panel electrical transfer connections

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection capacity

AWG

20~2AWG

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	101A
Rated current (D)	5A
Rated current (C)	101A

Electrical parameters IEC

Rated current	1000V
	125A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	25mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~125℃
---------------------------------	-----------

Accessories

--	--

Datos empresariales

Número de pedido	12010000308
Unidad de embalaje	6
Cantidad mínima de pedido	/
Peso del producto (sin embalaje)	132