


Visión general

Información del Producto



DG638-9.52-DA-10040000796

PCB terminal blocks, Rated current: 32A, Rated voltage (III/2) 1000V, Cross section: 0.2~4.0mm², pitch: 9.52mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

Ventajas del producto

- ☒ Fixed screw connection technology, safe and reliable
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~6mm²

Conductor cross section flexible

0.2~4.0mm²

AWG

30~10AWG

Torque

0.8N.m

Strip length

8mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated current (B)	30A
Rated current (C)	30A

Electrical parameters IEC

Rated voltage	1000V
Rated current(III/3)	690V
Rated current	32A
Rated current(III/2)	1000V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Pitch	9.52mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
---------------------	---------------------------

Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL 1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accesorios

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

Datos empresariales

Número de pedido	10040000796
Unidad de embalaje	465
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	6.23

