

Visión general

Información del Producto



DG271V-3.5-10060002860

PCB spring terminal blocks, Rated current: 17.5A. Rated voltage
(III/2) : 200V, pitch: 3.5mm, Color: green, Contact surface : Tin

Ventajas del producto

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method, suitable for various situations

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~1.5mm²

Conductor cross section flexible

0.2~1.5mm²

AWG

24~16AWG

Strip length

10mm

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

10A

Electrical parameters IEC

Rated voltage	200V
Rated current(III/3)	160V
Rated current	17.5A
Rated current(III/2)	200V
Rated current(II/2)	400V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	3.5mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accesorios

Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Datos empresariales	
Número de pedido	10060002860
Unidad de embalaje	400
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	1.129