

Visión general

Información del Producto



DG208-5.0-10060000703

PCB spring terminal blocks, Rated current: 9A. Rated voltage
(III/2) : 450V, pitch: 5.0mm, Color: gray, Contact surface : Tin

Ventajas del producto

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~0.75mm²

Conductor cross section flexible

0.2~0.75mm²

AWG

20~16AWG

Strip length

7mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	7A
Rated current (D)	7A

Electrical parameters IEC

Rated voltage	450V
Rated current	9A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Push-in spring connection
Pitch	5mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accesorios	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Datos empresariales	
Número de pedido	10060000703
Unidad de embalaje	500
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	1.206