


Visión general

Información del Producto

**2EDGKCM-7.62-10010002211**

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/2): 400V, pitch: 7.62mm, Color: green, Contact surface: Tin

Ventajas del producto

- ✓ Adapt to multi-type sockets, device design is highly flexible
- ✓ Keying requirements can be met
- ✓ Universal installation method, suitable for various situations

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	28~12AWG
Torque	0.5N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A

Rated current (D)	10A
Rated current (C)	15A

Electrical parameters IEC

Rated voltage	320V
Rated current	20A
Rated current(III/2)	320V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	90°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accesorios	
Tool	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	/
Accessories	
Coding strip	2EDG-PWI
Bridge	/
Marking strip	/
Others	/

Datos empresariales	
Número de pedido	10010002211
Unidad de embalaje	100
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	7.211