


Visión general

Información del Producto

**2EDGKBM-7.5-10010004231**

Pluggable terminal blocks, Rated current: 10A. Rated voltage
(III/2) : 400V, pitch: 7.5mm, Color: green, Contact surface : Tin

Ventajas del producto

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Universal installation method, suitable for various situations

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection capacity

Conductor cross section solid	1.0~2.5mm ²
Conductor cross section flexible	1.0~2.5mm ²
AWG	28~12AWG
Torque	0.6N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A

Rated current (D)	10A
-------------------	-----

Electrical parameters IEC

Rated voltage	400V
Rated current	18A
Rated current(III/2)	400V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	90°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	7.5mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Accesorios

Datos empresariales

Número de pedido	10010004231
Unidad de embalaje	350
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	7.328