


Visión general

Información del Producto

**15EDGVC-2.5-10030000638**

Pluggable terminal blocks, Rated current: 5A. Rated voltage
(II / 2) : 250V, pitch: 2.5mm, Color: green, Contact surface : Tin

Ventajas del producto

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is perpendicular to PCB

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	150V
Rated voltage (C)	150V
Rated voltage (D)	150V
Rated current (B)	4A
Rated current (D)	4A
Rated current (C)	4A

Electrical parameters IEC

Rated voltage	250V
Rated current	5A
Rated current(II/2)	250V
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	2.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI-2.5

Datos empresariales	
Número de pedido	10030000638
Unidad de embalaje	500
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	0.46