


Visión general

Información del Producto

**15EDGKNM-3.5-10020002326**

Pluggable terminal blocks, Rated current: 8A. Rated voltage
(III/2) : 250V, Cross section: 1.0mm², pitch: 3.5mm, Color: green, Contact surface
: Tin

Ventajas del producto

- ✓ Adapt to multi-type sockets, device design is highly flexible
- ✓ PUSH-IN connection technology, fast wiring
- ✓ Universal installation method, suitable for various situations

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection capacity

Conductor cross section solid	0.2~1.0mm ²
Conductor cross section flexible	0.2~1.0mm ²
AWG	28~16AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A

Rated current (D)	8A
-------------------	----

Electrical parameters IEC

Rated voltage	160V
Rated current(III/3)	160V
Rated current	8A
Rated current(III/2)	160V
Rated current(II/2)	250V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	3.81mm
Number of potentials	12
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accesorios	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Datos empresariales	
Número de pedido	10020002326
Unidad de embalaje	545
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	6.6