

Visión general

Información del Producto



DG2216R-10.0-DA-10050000853

PCB Terminal Blocks, Rated current: 76A, Rated voltage (III/2) : 1000V, Cross section: 16mm², Pitch: 10.0mm, Connection method: Push-in spring connection, Color: Green, Contact surface: Tin

Ventajas del producto

- ☒ Push-in spring connection, excellent anti-vibration performance, tool-free.
- ☒ Dual-Lever Spring patented technology, easy and comfortable operation.
(Chinese patent for Utility Model, patent application number ZL201921625513.6)
- ☒ Levers status is optional (open/close), suitable for multi-core cable.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection capacity

Conductor cross section solid	0.2~25mm ²
AWG	18~4AWG

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Connection capacity

Conductor cross section flexible	0.2~16mm ²
Strip length	18mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	66A
Rated current (D)	5A
Rated current (C)	66A

Electrical parameters IEC

Rated voltage	1000V
Rated current(III/3)	1000V
Rated current	76A
Rated current(III/2)	1000V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accesorios

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Datos empresariales

Número de pedido	10050000853
Unidad de embalaje	100
Cantidad mínima de pedido	

Peso del producto (sin embalaje)	24
----------------------------------	----