

Visión general

Información del Producto

**Bus IO-DF750-HT-200-11-1001A(H)-30050000227**

Card IO housing,push-instructure,16aisleInput and output module housing,with LED display,Gold finger connection is completely disconnected

Ventajas del producto

- ☑Hand-plugged, easy to assemble
- ☑Internal bus through bottom 6 gold-plated terminals
- ☑Equipped 16 channels functional module ,LEDs per node
- ☑Internal 2 gold-plated blade connectors for power cascading expansion
- ☑Can be installed on DIN rail

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Dimension

length

100mm

width

12mm (main module)

Height

66.8mm

Mechanical parameters

structure type

Compact terminal module housing with signal LED

Material

PC+PA66

installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Accesorios

Datos empresariales

Número de pedido	30050000227
Unidad de embalaje	200 SKT
Cantidad mínima de pedido	200 SKT
Peso del producto (sin embalaje)	40g