

Visión general

Información del Producto



Relay base-DPKF08A-E3-00A(H)-30020000049

DPKFrelay base,used for2PDTrelay,screw connection

Ventajas del producto

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 12A, 2PDTgrade
- ☒ Arc partition between adjacent columns
- ☒ Anti-touch cover at the top of the screw

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

☐

Dimension

length	69.6mm
width	25mm
Depth including bracket	29.2mm

Environmental data

Ambient temperature (storage/transport)	-40 °C ... +85 °C
Ambient temperature (operation)	-20 °C ... 50 °C

Technical data

Rated voltage UN	300V
Installation location	Arbitrary

Assembly instructions	DIN35 rail
-----------------------	------------

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Accesorios

Datos empresariales

Número de pedido	30020000049
Unidad de embalaje	20 SKT
Cantidad mínima de pedido	20 SKT
Peso del producto (sin embalaje)	62g