

Visión general

Información del Producto



Relay base-DPTF08A-3-00A(H)-30020000053

DPTFrelay base,used for2PDTrelay,screw connection

Ventajas del producto

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 10A, 2PDTgrade
- ☒ Arc partition between adjacent columns

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Dimension

length	71mm
width	30mm
Depth including bracket	27.5mm

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-40~+65℃

Technical data

Rated voltage UN	300V
Rated current IN	10A

Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Accesorios

Datos empresariales

Número de pedido	30020000053
Unidad de embalaje	
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	