


Visión general

Información del Producto

**2CDGVM-5.08-10030001081**

Pluggable Terminal Blocks nominal current 12A. Rated voltage (III/2): 320V, pitch: 5.08mm, Color: green, Contact surface: Tin

Ventajas del producto

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Through-wall installation, free positioning

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current	12A

Rated current(III/2)	320V
Rated surge voltage(III/2)	2KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accesorios

Tool

Screwdriver	/
-------------	---

Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	2EDG-PWP-01A(H)

Datos empresariales	
Número de pedido	10030001081
Unidad de embalaje	
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	