

Visión general

Información del Producto



DG25H-B-12020000054

Single layer PCB fence terminal,nominal current15A.Rated voltage(UL): 300V,Rated cross section:22~14AWG,pitch:7.62mm,Color:black,Contact surface:Tin

Ventajas del producto

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Solder board installation, which can realize the electrical connection between the device and the PCB

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection capacity

AWG	22~14AWG
Torque	0.5N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Item properties

Type of installation	PCB welding
----------------------	-------------

Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M3
Pitch	7.62mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accesorios

Accessories

--	--

Datos empresariales

Número de pedido	12020000054
------------------	-------------

Unidad de embalaje	830
Cantidad mínima de pedido	/
Peso del producto (sin embalaje)	4.584