

Visión general

Información del Producto



DG97-A-12050000147

Transfer Type,nominal current60A.Rated voltage(UL): 300V,Rated cross section:22~3AWG,pitch:12mm,Color:black,Contact surface:Tin

Ventajas del producto

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Provide the cabinet and panel electrical transfer connections

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

□

Wiring capacity

torque	3N.m
Connectable conductor cross section	22~3AWG

Device properties

spacing	12mm
---------	------

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	300V
Rated current (B)	60A
Rated current (D)	10A

Rated current (C)	60A
-------------------	-----

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M6
Number of potentials	12
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Accesorios

Accessories

--	--

Datos empresariales	
Número de pedido	12050000147
Unidad de embalaje	8
Cantidad mínima de pedido	/
Peso del producto (sin embalaje)	402.7