

Visión general

Información del Producto



RM-EBBH-2006-M-1000-00A(H)-250800000001

Charging and discharging plug at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance > 500M Ω; Protection grade: IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 20N; Working temperature: - 40 ~ 105 °C; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

Ventajas del producto

- ☑ Compact structure and high space utilization
- ☑ Adopt bayonet locking structure to prevent accidental unlocking
- ☑ Direct plug operation, convenient and fast
- ☑ Signal pin No.: 0~8 pins
- ☑ Multiple auditory and visual feedback are inserted in place
- ☑ Beautiful appearance, fit human functional design

Certificación del producto

RoHS

Datos técnicos

Dibujo del producto

Modelo 3D

□

Marking

Series	DA
	DD
	DF

versions

Connection method	Crimping connection
Female/Male	Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
	48B
Number of positions	15
	25
	32
	42
parámetro técnico	
Resistencia de aislamiento	≥500MΩ
Vida mecánica	≥3000次
Parámetros ambientales	
Nivel de protección	MatchingIP67

Accesorios

Datos empresariales	
Número de pedido	25080000001
Unidad de embalaje	
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	