


## Visión general

### Información del Producto



### DG75-A-12050000239

Up and down transfer terminal, nominal current: 75A. Rated voltage (UL): 600V, rated cross section: 22~4AWG, pitch: 16mm, color: black, contact surface: tin

### Ventajas del producto

- ☒ Screw connection for worldwide use
- ☒ Barrier wiring structure, stable and reliable connection
- ☒ It can meet the high current electrical connection at the power end

### Certificación del producto



## Datos técnicos

### Dibujo del producto

### Modelo 3D

□

### Wiring capacity

torque

5N.m

### Electrical parameters UL

Rated current (B)

75A

Rated current (C)

75A

### Connection capacity

AWG

22~4AWG

### Electrical parameters UL

Rated voltage (B)

600V

|                   |      |
|-------------------|------|
| Rated voltage (C) | 600V |
| Rated voltage (D) | 600V |
| Rated current (D) | 5A   |

Item properties

|                      |                               |
|----------------------|-------------------------------|
| Type of installation | panel                         |
| Pin arrangement      | Single row in a straight line |
| Connection method    | Screw connection              |
| Screwdriver          | Phillips screwdriver          |
| screw thread         | M6                            |
| Pitch                | 16mm                          |
| Number of potentials | 1                             |
| Pluggable or not     | no                            |
| Number of rows       | 1                             |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | Nickel plating            |
| Insulation Materials        | PBT                       |
| Insulating material group   | IIIa                      |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |        |
|--------------------|--------|
| Test Specification | UL1059 |
|--------------------|--------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~120℃ |
|---------------------------------|-----------|

|            |
|------------|
| Accesorios |
|            |

|                                  |             |
|----------------------------------|-------------|
| Datos empresariales              |             |
| Número de pedido                 | 12050000239 |
| Unidad de embalaje               | 45          |
| Cantidad mínima de pedido        | /           |
| Peso del producto (sin embalaje) | 66          |