


Visión general

Información del Producto

**15EDGKG-3.5-10010008888**

Pluggable terminal blocks, Rated current: 7A. Rated
voltage (U_i/U_e): 250V, pitch: 3.5mm, Color: green, Contact surface: Tin

Ventajas del producto

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Universal installation method, suitable for various situations

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Durability test

Sea level impulse withstanding voltage

2.95kV

Packaging information

Type of packaging

bag packaging

Connection capacity

Conductor cross section solid

0.5~1.5mm²

Conductor cross section flexible

0.5~1.5mm²

feeler gauge a x b / diameter

2.4mm x 1.5mm / 1.6mm

AWG

28~16AWG

Torque	0.2N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A
Rated current (D)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	7A
Rated current(II/2)	250V
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated

Contact zone metal surface	tin-plated
Insulation Materials	PA66
Shell color	green
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accesorios

Tool

Screwdriver	0.4x2.5,Slotted screwdriver
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Datos empresariales

Número de pedido	10010008888
Unidad de embalaje	300
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	3.36

