


## Visión general

### Información del Producto



#### DGV10-10090000027

Through-wall terminal blocks, Rated current: 57A, Rated voltage (III/3) : 400V, width: 10.1mm, Color: gray, Contact surface :Tin

### Ventajas del producto

- ☒ Screw connection technology,safe and reliable
- ☒ Through-wall installation, free positioning

### Certificación del producto



## Datos técnicos

### Dibujo del producto

### Modelo 3D

□

### Connection capacity

|                                  |                       |
|----------------------------------|-----------------------|
| Conductor cross section solid    | 0.5~16mm <sup>2</sup> |
| Conductor cross section flexible | 0.5~10mm <sup>2</sup> |
| AWG                              | 24~6AWG               |
| Torque                           | 1.2N.m                |
| Strip length                     | 10mm                  |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 150V |
| Rated voltage (D) | 300V |

|                   |     |
|-------------------|-----|
| Rated current (B) | 65A |
| Rated current (D) | 10A |
| Rated current (C) | 65A |

Electrical parameters IEC

|                            |      |
|----------------------------|------|
| Rated current(III/3)       | 400V |
| Rated current              | 400V |
|                            | 57A  |
| Rated surge voltage(III/3) | 6KV  |

Item properties

|                      |                     |
|----------------------|---------------------|
| Type of installation | panel               |
| Connection method    | Screw connection    |
| Screwdriver          | Slotted screwdriver |
| screw thread         | M4                  |
| Number of potentials | 1                   |
| Pluggable or not     | Yes                 |
| Number of rows       | 1                   |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                 |
|--------------------|-----------------|
| Test Specification | UL1059/IEC60998 |
|--------------------|-----------------|

Environmental data

|                                 |             |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~105°C |
|---------------------------------|-------------|

Accesorios

|                |                               |
|----------------|-------------------------------|
| tool           |                               |
| screwdriver    | 0.8x4.0mm,Slotted screwdriver |
| Operating tool | /                             |

|               |          |
|---------------|----------|
| Accessories   |          |
| Coding strip  | /        |
| Marking strip | ZB10     |
| Bridge        | EB xx-10 |
| Other         | /        |

|               |      |
|---------------|------|
| Accessories   |      |
| Coding strip  | /    |
| Bridge        | /    |
| Marking strip | ZB10 |
| Others        | /    |

|                |                                |
|----------------|--------------------------------|
| Tool           |                                |
| Operating tool | /                              |
| Screwdriver    | 1.0x4.0mm, Slotted screwdriver |

Datos empresariales

|                           |             |
|---------------------------|-------------|
| Número de pedido          | 10090000027 |
| Unidad de embalaje        | 50          |
| Cantidad mínima de pedido |             |

|                                  |       |
|----------------------------------|-------|
| Peso del producto (sin embalaje) | 21.78 |
|----------------------------------|-------|