


Visión general

Información del Producto

**DS2.5-TG-11040000207**

Disconnect terminal blocks, connector method: Push-in connector, Rated voltage : 400 V, Rated current : 20 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 26 - 12, Width: 5.2 mm, Color: gray, Mounting type: NS35/7.5, NS35/15

Ventajas del producto

- ☑ Disconnect terminal blocks.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ The circuit can be disconnected, measured, controlled easily by operate the knife disconnecter.
- ☑ Equipped with test holes on both sides of the breaking point, convenient for testing the circuit.
- ☑ Snap-on knife disconnecter to prevent accidental disconnection.
- ☑ Universal breaking area to achieve different functions, can insert breaking plug, component plug, fuse plug.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D



Overview

Connection method	Push in connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	62mm
width	5.2mm

Wiring data

Strip length	10~12mm
Conductor cross section solid AWG	26~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	400V
Rated surge voltage	6KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Accesorios

Marker

Top marker	ZB5 / ZS5
Side marker	ZSF5
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
---	---------

Bridge	DFBXX-5.2
End cover	D-DS2.5-MT
Matching accessories	DS-DI / DS-CO / DS-FU5 / DS-FU5-LD24

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Datos empresariales

Número de pedido	11040000207
Unidad de embalaje	100
Cantidad mínima de pedido	100
Peso del producto (sin embalaje)	7.78