


## Visión general

## Información del Producto

**DSKK1.5-PE-11040000195**

Double-level terminal block, connector method: Push-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 26 - 14, Width: 3.5 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

## Ventajas del producto

- ☑ Double-level terminal block.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Unique plug-in bridge, high circuit connection efficiency.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

## Certificación del producto



## Datos técnicos

## Dibujo del producto

## Modelo 3D



## Overview

|                                           |                    |
|-------------------------------------------|--------------------|
| Connection method                         | Push in connection |
| Number of rows                            | 2                  |
| number of connections                     | 4                  |
| Open-end side panels                      | Yes                |
| Insulation Materials                      | PA                 |
| Flame retardant grade, in line with UL 94 | V0                 |

## Dimension

|                 |        |
|-----------------|--------|
| End plate width | 1.5mm  |
| length          | 68.2mm |
| width           | 3.5mm  |

#### Wiring data

|                                   |                          |
|-----------------------------------|--------------------------|
| Strip length                      | 8~10mm                   |
| Conductor cross section solid     | 0.14~1.5mm <sup>2</sup>  |
| Conductor cross section flexible  | 0.14~1.5 mm <sup>2</sup> |
| Conductor cross section solid AWG | 26~14                    |

#### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

#### IEC Electrical parameters

|                     |     |
|---------------------|-----|
| Rated surge voltage | 6KV |
|---------------------|-----|

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

### Accesorios

#### Marker

|                |        |
|----------------|--------|
| Top marker     | /      |
| Side marker    | ZSF3.5 |
| Marker support | /      |

#### Accessories

|                                                       |           |
|-------------------------------------------------------|-----------|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.4x2.5   |
| Bridge                                                | DFBXX-3.5 |

|                               |                                       |
|-------------------------------|---------------------------------------|
| End cover                     | D-DSKK1.5                             |
| Installation                  |                                       |
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

Datos empresariales

|                                  |             |
|----------------------------------|-------------|
| Número de pedido                 | 11040000195 |
| Unidad de embalaje               | 100         |
| Cantidad mínima de pedido        | 100         |
| Peso del producto (sin embalaje) | 8.06        |