

Visión general

Información del Producto



DG150-A-12010001050

Up and down transfer terminal, nominal current: 150A, Rated voltage: 1000A, Pitch: 27mm, Color: black, Contact surface: Ni

Ventajas del producto

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ High current electrical connections at power end can be met

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Wiring capacity

torque

5.6N.m

Connectable conductor cross section

6~1/0 AWG

Electrical parameters UL

Rated voltage

1000V

Rated current

150A

Item properties

Type of installation

panel

Pin arrangement

Single row in a straight line

Connection method

Screw connection

Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	27mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials (main class)	PA66+GF
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~120°C
---------------------------------	-------------

Accesorios

Datos empresariales

Número de pedido	12010001050
Unidad de embalaje	12
Cantidad mínima de pedido	12

Peso del producto (sin embalaje)	2448
----------------------------------	------