


Visión general

Información del Producto



DCTK6-20A(H)-11020000234

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 630 V, Rated current: 41 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm² - 6 mm², AWG: 22 - 8, Width: 8 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Ventajas del producto

- ☒ Current terminal;
- ☒ Steel screw connection technology, reliable connection;
- ☒ The sliding block breaks, which can realize the circuit breaking function;
- ☒ The box has a baffle to prevent mis-insertion;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

UL Electrical parameters

Rated current

45A

Overview

Connection method

screw connection

Number of rows

1

number of connections

2

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94	V0
---	----

Dimension

NS 35/7,5 Height	46.55mm
End plate width	1.5mm
NS 35/15 Height	54.05mm
length	70.9mm
width	8mm
Height	46.1mm

Wiring data

Screw type	Slotted screw
Strip length	10~11mm
Conductor cross section solid	0.5~6mm ²
Conductor cross section flexible	0.5~6mm ²
Conductor cross section solid AWG	22~8
screw thread	M4
Tightening torque	1.2N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	630V
Rated current (III / 3)	41A
Rated surge voltage	8KV

Environmental protection

REACH SVHC	Lead 7439-92-1
------------	----------------

RoHS

No excessive harmful substances

Accesorios

Marker

Top marker

/

Side marker

ZB8

Marker support

/

Accessories

Slotted screwdriver size (Blade thickness x Width)

1×4

Bridge

FBR16-RTK/S-XXP

End cover

D-DCTK6

Partition plate

/

Installation

End clamp

E-WS N / E-PC-1100A

Terminal strip marker support

KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2

DIN rail

NS35/7.5 & NS35/15

Datos empresariales

Número de pedido

11020000234

Unidad de embalaje

50

Cantidad mínima de pedido

50

Peso del producto (sin embalaje)

20.967