


Visión general

Información del Producto



DC50-11020000216

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 1000 V, Rated current: 150 A, Number of connectors: 2, Number of potentials: 1, Cross section: 16 mm² - 50 mm², AWG: 6 - 1/0, Width: 20 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Ventajas del producto

- ☒ Steel screw connection technology, reliable connection;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

UL Electrical parameters

Rated current

125A

IEC Electrical parameters

Rated current (III / 3)

150A

Overview

Connection method

screw connection

Number of rows

1

number of connections

2

Open-end side panels

no

Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

Height	75.85mm
NS 35/7,5 Height	75.9mm
NS 35/15 Height	83.4mm
length	70.45mm
width	20mm

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	10-16mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	16-50mm ²
Conductor cross section flexible (ferrule without plastic sleeve)	16-50mm ²
Strip length	22~23mm
Conductor cross section solid	16~50mm ²
Conductor cross section flexible	16~50mm ²
Conductor cross section solid AWG	6~1/0
screw thread	M6
Tightening torque	2.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	1000V
-------------------------	-------

Rated surge voltage	8KV
Environmental protection	
REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Accesorios	
Marker	
Top marker	/
Side marker	ZT12
Marker support	/
Accessories	
Slotted screwdriver size (Blade thickness x Width)	1.2×8
Bridge	FBI2-20 / FBI3-20
End cover	/
Partition plate	/
Installation	
End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Datos empresariales	
Número de pedido	11020000216
Unidad de embalaje	10
Cantidad mínima de pedido	10
Peso del producto (sin embalaje)	115.365

