

Visión general

Información del Producto



DCKKB10-11020000183

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 500 V, Rated current: 57 A, Number of connectors: 4, Number of potentials: 1, Cross section: 0.5 mm² - 10 mm², AWG: 20 - 6, Width: 10 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Ventajas del producto

- ☒ Steel screw connection technology, reliable connection;
- ☒ Equipped with dual-channel bridge wells, circuit connection testing is more flexible;
- ☒ Unique plug-in bridge, high circuit connection efficiency;
- ☒ The box has a baffle to prevent mis-insertion;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

UL Electrical parameters

Rated current

65A

Overview

Connection method

screw connection

Number of rows

2

number of connections

4

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94	V0
---	----

Dimension

Height	71.2mm
NS 35/7,5 Height	72.5mm
End plate width	1.5mm
NS 35/15 Height	80mm
length	83.9mm
width	10mm

Wiring data

Screw type	Slotted screw
Strip length	10~12mm
Conductor cross section solid	0.5~10mm ²
Conductor cross section flexible	0.5~10mm ²
Conductor cross section solid AWG	20~6
screw thread	M4
Tightening torque	1.54N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	57A
Rated surge voltage	6KV

Environmental protection

REACH SVHC	Lead 7439-92-1
------------	----------------

RoHS

No excessive harmful substances

Accesorios

Marker

Top marker

/

Side marker

ZB10

Marker support

/

Accessories

Slotted screwdriver size (Blade thickness x Width)

1×4

Bridge

DFA10

End cover

D-DCKKB10

Partition plate

/

Installation

End clamp

E-WS N / E-PC-1100A

Terminal strip marker support

KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2

DIN rail

NS35/7.5 & NS35/15

Datos empresariales

Número de pedido

11020000183

Unidad de embalaje

20

Cantidad mínima de pedido

20

Peso del producto (sin embalaje)

39.45