

Visión general

Información del Producto



DC4-12A(H)-11020000059

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 1000 V, Rated current: 32 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm² - 4mm², AWG: 22 - 10, Width: 6.1 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Ventajas del producto

- ☒ Steel screw connection technology, reliable connection;
- ☒ Equipped with dual-channel bridge wells, circuit connection testing is more flexible;
- ☒ Unique plug-in bridge, high circuit connection efficiency;
- ☒ The box has a baffle to prevent mis-insertion;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

NS 35/7,5 Height	41.5mm
End plate width	1.5mm
NS 35/15 Height	49mm
length	44.5mm
width	6.1mm
Height	40mm

Wiring data

Screw type	Cross & Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-2.5mm ²
Conductor cross section flexible (ferrule without plastic sleeve)	0.5-4mm ²
Strip length	8~9mm
Conductor cross section solid	0.5~6mm ²
Conductor cross section flexible	0.5~4mm ²
Conductor cross section solid AWG	22~10
screw thread	M3
Tightening torque	0.6N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	1000V
Rated current (III / 3)	32A
Rated surge voltage	8KV

Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

Accesorios

Marker

Top marker

/

Side marker

ZB6

Marker support

/

Accessories

Slotted screwdriver size (Blade thickness x Width)

0.6×3.5

Bridge

DFA4

End cover

D-DC2.5

Partition plate

/

Installation

End clamp

E-WS N / E-PC-1100A

Terminal strip marker support

KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2

DIN rail

NS35/7.5 & NS35/15

Datos empresariales

Número de pedido

11020000059

Unidad de embalaje

100

Cantidad mínima de pedido

100

Peso del producto (sin embalaje)

6.233