


Visión general

Información del Producto

**DC2.5-QU-11020000214**

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 500 V, Rated current: 24 A, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 28 - 12, Width: 5.1 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Ventajas del producto

- ☑ Steel screw connection technology, reliable connection;
- ☑ Equipped with dual-channel bridge wells, circuit connection testing is more flexible;
- ☑ Unique plug-in bridge, high circuit connection efficiency;
- ☑ The box has a baffle to prevent mis-insertion;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D



Overview

Connection method	screw connection
Number of rows	1
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

NS 35/7,5 Height	49.2mm
End plate width	1.5mm
NS 35/15 Height	56.7mm
length	54.4mm
width	5.1mm
Height	47.7mm

Wiring data

Screw type	Cross & Slotted screw
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-1.5mm ²
Strip length	8~9mm
Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~2.5mm ²
Conductor cross section solid AWG	28~12
screw thread	M2.5
Tightening torque	0.4N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	24A
Rated surge voltage	6KV

Environmental protection

REACH SVHC	Lead 7439-92-1
------------	----------------

RoHS

No excessive harmful substances

Accesorios

Marker

Top marker

/

Side marker

ZB5 / WB5

Marker support

/

Accessories

Slotted screwdriver size (Blade thickness x Width)

0.6×3.5

Bridge

DFA2.5

End cover

D-DC4-QU

Partition plate

/

Installation

End clamp

E-WS N / E-PC-1100A

Terminal strip marker support

KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2

DIN rail

NS35/7.5 & NS35/15

Datos empresariales

Número de pedido

11020000214

Unidad de embalaje

100

Cantidad mínima de pedido

100

Peso del producto (sin embalaje)

8.17