

## Visión general

### Información del Producto



## WSF4-TA-10A(H)-11030000759

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 10 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup>- 4 mm<sup>2</sup>, AWG: 28 - 12, Width: 6 mm, Fuse type: Glass / ceramics / ..., Fuse type: G / 5 x 20, Color: black, Mounting type: NS 35/7.5, NS 35/15.

### Ventajas del producto

- ☒ WS Fuse wire terminal;
- ☒ spring-cage connection technology, good anti-vibration performance;
- ☒ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☒ Unique plug-in bridge, high circuit connection efficiency;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

### Certificación del producto



## Datos técnicos

### Dibujo del producto

### Modelo 3D

□

### Overview

|                                           |                        |
|-------------------------------------------|------------------------|
| Connection method                         | spring-cage connection |
| Number of rows                            | 1                      |
| number of connections                     | 2                      |
| Open-end side panels                      | no                     |
| Insulation Materials                      | PA                     |
| Flame retardant grade, in line with UL 94 | V0                     |
| fuse                                      | G/5 x 20               |

|           |                   |
|-----------|-------------------|
| Fuse type | Glass/ceramic/... |
|-----------|-------------------|

#### Dimension

|                  |        |
|------------------|--------|
| NS 35/7,5 Height | 68mm   |
| NS 35/15 Height  | 75.5mm |
| length           | 60mm   |
| width            | 6mm    |
| Height           | 66.6mm |

#### Wiring data

|                                   |                      |
|-----------------------------------|----------------------|
| Strip length                      | 10~12mm              |
| Conductor cross section solid     | 0.2~4mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~4mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~12                |

#### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

#### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 400V |
| Rated current (III / 3) | 10A  |
| Rated surge voltage     | 6KV  |

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

#### Accesorios

#### Marker

|                |      |
|----------------|------|
| Top marker     | ZB6  |
| Side marker    | /    |
| Marker support | /    |
| Warning cover  | EEA4 |

Accessories

|                                                    |         |
|----------------------------------------------------|---------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5 |
| Adjacent jumper (2P)                               | WFA4    |
| Alternate jumper (2P)                              | WFB4    |
| Staggered jumper (2P)                              | /       |
| End cover                                          | /       |

Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

Datos empresariales

|                                  |             |
|----------------------------------|-------------|
| Número de pedido                 | 11030000759 |
| Unidad de embalaje               | 115         |
| Cantidad mínima de pedido        | 115         |
| Peso del producto (sin embalaje) | 13.4        |